

## Angle Grinder 125 mm

# GA5091



### Product Description

1 900 W • 125 mm • 2 800 - 11 500 min<sup>-1</sup>

**Corded angle grinder with improved power consumption and durability**

GA5091 Angle Grinder has SJS II technology, Active Feedback sensing Technology, Anti-Restart Function, Mechanical Brake, Soft Start and Slide Switch.

### Product Features

- ⦿ Anti-restart function minimizes accidental start-up
- ⦿ AFT (Active Feedback sensing Technology) turns the motor off if rotation speed suddenly slows or wheel is forced to stop
- ⦿ Super Joint System II developed for effective vibration absorption

### Barcode

88381768443

### Product Specifications

Power Supply Cord UK	2,5 m
Bore Size (Arbor Diameter)	22,23 mm
Vibration Level, Surface Grinding	8,7 m/s <sup>2</sup>
Max. Depth of Cut	31 mm
Grinding Disc Diameter	125 mm
Vibration Uncertainty (K Factor), Disc Sanding	1,5 m/s <sup>2</sup>
Sound Pressure Level	90 dB(A)
Vibration Level, Disc Sanding	3,0 m/s <sup>2</sup>
Power Supply Cord	4,0 m
Continuous Input Power	1900 W
Product Dimensions (L x W x H):	349 x 140 x 129 mm
Sound Power Level (L <sub>WA</sub> )	98 dB(A)
Spindle Thread	M14
Weight Without Cable (EPTA)	2,8 - 4,0 kg
Noise Uncertainty (K Factor)	3 dB(A)
Max Output Power	2100 W
Vibration Uncertainty (K Factor), Surface Grinding	1,5 m/s <sup>2</sup>
Anti-Restart Function (NVR Switch)	1
Tool Category	Grinding, Sanding and Polishing
No load speed	2800 - 11500 min <sup>-1</sup>

### More info

<https://makita.co.tz/product/angle-grinder-125-mm-ga5091/>